

Adhesive

UK-8160-UK-5400-3.6KG-LOCTITE - UK-8160-UK-5400-3.6KG-LOCTITE

<https://www.123bearing.co.uk/lubricant-adhesive/adhesive/adhesive/uk-8160-uk-5400-3.6kg-loctite>

TYPE	Polyuréthane
DESCRIPTION	Colle d'assemblage, PU Bicomposant, pâte
NOUVEAU NOM	
ANALYSE	LOCTITE UK 8160/UK 5400
CONDITIONNEMENT	KI 3.6 kg
COMMENTAIRE	-
APPROBATION	0

Description

LOCTITE® UK 8160 / LOCTITE® UK 5400 is a light brown, 2-part, solvent-free, polyurethane-based paste adhesive. A weight mix ratio of 5:1 with LOCTITE UK 5400 produces a hard elastic product (glue) for elastic, bend-resistant bonding of pre-treated metals, wood and plastics with rigid foams. It is used in making sandwich elements and in engineering insulation down to -30 °F (-190 °C).

Avantages

Solvent-free
Polyurethane-based
Very high viscosity - highly paste
Certified acc. IMO 653, Part 5 / IMO MSC 61 (shipbuilding)
Proven advantages for the repair of composite elements (level out)
Can be used in temperatures down to -30 °F (-190 °C)

Caractéristiques

2 part, solvent-free, polyurethane-based paste adhesive used in the bonding of pre-treated metals, wood and plastics with rigid foams.

PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	4033267282076
Type	MASTICS ET COLLES
Weight	4106 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE